

Industrial HMI Operator Panel NK03

HMI
N SERIES




Features

- ARM 9 (400 MHz)
- 3.5" TFT 320 x 240, 300 cd/m², 20,000 hours
- Come with function and numeric keys
- 19.2 ~ 28.8V, Isolated Power
- Plastic chassis, fan-less design
- Panel mount, IP65 front bezel
- Suitable for industrial applications

Specifications

CPU	ARM 9 (400 MHz)
Memory	128MB SDRAM
Storage	128MB NAND Flash
I/O	1 x USB 1.1 host Type A 1 x USB 2.0 device Type B 1 x RS232 1 x RS422/485, COM1 Function keys (F1 ~ F11) Numeric Keys (0-9 , A-F)
Display	3.5" TFT, 320 x 240 Luminance 300 (cd/m ²) View angle 140/130 (H°/V°) Backlight Lifetime 20,000 hours Contrast ratio 500:1
Touch Screen	-
Power	19.2 ~ 28.8V Isolated Power
Construction	Plastic
Net Weight(Kgs)	0.33 Kg
Mounting	Panel mount
Dimensions (mm)	178(W) x 107.3(H) x 49.5(D)
Operating Temp.	0°C ~ 50°C
Storage Temp.	-20°C ~ 60°C
Humidity	10% to 90% @ 40°C, (non-condensing)
Certification	CE/FCC (EN 61000-6-4, EN 61000-6-2)



Ordering Information

NK03-P

3.5" TFT 320 x 240 fan-less keypad HMI with ARM 9 (400 MHz) CPU, 128MB RAM, 128M Flash, 19.2 ~ 28.8V isolated power, painted plastic chassis and IP65 front bezel

NOVAKON